

Cosmolubric HF-130

DESCRIPTION

Cosmolubric HF-130 is a Factory Mutual approved high quality synthetic polyol ester hydraulic fluid. Chemically and thermally stable, Cosmolubric HF-130 was designed for long life and dependable performance in areas where a less flammable hydraulic fluid should be used.

Besides having good thermal stability, Cosmolubric HF-130 exhibits a good temperature/viscosity relationship or Viscosity Index. Cosmolubric HF-130 also contains an additive package, formulated in our laboratory and proven in the field, to give the best possible performance, corrosion protection, metal passivation, hydrolytic stability and oxidation inhibition.

DATA (TYPICAL VALUES)

Appearance	Clear amber, mobile fluid
ISO Viscosity Grade	68
Viscosity, SUS	
@ 0°F	8850
@ 32°F	2150
@ 100°F	305
@ 210°F	68
Viscosity Index	>200
Total Acid Number, mg KOH/g	3.0
Specific Gravity, 60/60°F	0.92
Pounds per Gallon, 60°F	7.7
Flash Point	575°F (302°C)
Fire Point	615°F (325°C)
Pour Point	-10°F (-23°C)
Rust Test (ASTM D-665A)	Pass
Copper Strip Tarnish Test (ASTM D-130) Condition of panel	lb

Date | version
Code

FEATURES/ BENEFITS

- Factory Mutual Approved as a fire resistant hydraulic fluid that protects personnel and property from accidental fire and may lower insurance premiums
- Fluid is a GREEN product that is composed of renewable resources
- Provides excellent lubrication characteristics which extends pump and component life
- High viscosity index allows the fluid to be used at a wide temperature range
- Contains additives to enhance oxidation stability that will extend service life
- Hydrolytically stable to resist degradation when water contamination is present

PUMP TEST

ASTM D-2882 procedure Vickers V-104-C pump

TEST CONDITIONS

Test Period, hour	100
Discharge Pressure, psi	2000
Fluid Temperature, °F	150
Pump Speed, rpm	1200
Output Volume, GPM	7.5

TEST RESULTS

Total wear on ring and vane set, mg	<15
-------------------------------------	-----

HEALTH AND SAFETY

Refer to MSDS for proper handling and disposal. Please note that the MSDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local Houghton representative.

NOTE: Read and understand all precautions on container labels before using this product.



Houghton International Inc.
Madison and Van Buren Aves.
P. O. Box 930
Valley Forge, PA 19482-0930

Phone: 610-666-4000
Fax: 610-666-0174
info@houghtonintl.com
www.houghtonintl.com

This document contains information based on data that is believed to be correct. However, the product may not be applicable to all uses and operating environments. No warranty or guarantee is expressed or implied.