

Granville Diamond 0W/40

1 Litre, 25 Litre & 199 Litre

Product Description

Granville Diamond 0W/40 is a low viscosity fuel efficient engine oil for modern high performance petrol & diesel engines, both multi-valve and turbo charged. Gives excellent engine protection on cold start up in extremely cold conditions.

Recommended for use by Granville for the following manufacturer's specifications

ACEA A3/B3
API SJ/CF
BMW Longlife
MB 229.3
Porsche
VW 502.00
VW 503.00
VW 505.00



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0082	5020618000822
25 Litre	0115	5020618001157
199 Litre	0112	5020618001126

Product Benefits

- * Ensures lubricant performance over extended drain intervals
- * Excellent high & low temperature performance
- * Outstanding fuel efficiency
- * Effective environmental protection

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Shelf Life

5 years from date of manufacture.

Appearance	: Amber liquid
Odour	: Characteristic
Specific Gravity	: 0.863 @ 15.6°C (typical)
Solubility	: Insoluble in water
Flashpoint	: >200°C



TECHNICAL

Data

Granville Diamond 0W/40

1 Litre, 25 Litre & 199 Litre



Kinematic Viscosity @ 40°C : 90.7 cSt (typical)

Kinematic Viscosity @ 100°C : 15.4 cSt (typical)

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 1 | Date: 16/03/2012

